


## HIK SERIES P2.5 INDOOR LED DISPLAY

HIK series LED solutions deliver unrivalled versatility due to the variety of cabinet configurations available. Integrators specifying the HIK range have access to the broadest range of pixel pitch and aspect ratios options. Perfect for any internal space, these innovative Hisense LED modules include cable-less internal construction and full frontal access for ease of maintenance.



### Highlights



#### High refresh rate

With uniform color scale and brightness, dynamic performance of LED display could restore the true scenes without any ripples.



#### Brightness nits

With an average 500 nits and 1,000 nits maximum brightness, the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



#### Low brightness & High gray level

LED display could reveal more details, including layers and colors, than traditional displays do.



#### 160° High viewing angle

The extra wide 160° viewing angle is a perfect fit for large groups of people that will view the displays from diverse angles while passing by.



#### High color calibration

LED display correction technology could uniformly lighten several hundred thousand LED lights, presenting a uniform display effect with the same brightness and color scale.



#### AOB Admixture on board

AOB Transparent glass on surface enhances the mixed light property with scratch resistance, water-proof & easy to clean.



## Specifications

### HIK Series

Pixel Pitch	P2.5
LED Type	SMD2121 3in1
Thickness	53.7mm / 2.11 inch
Module Size (W/H)	240 x 270mm / 9.45 x 10.63 inch
Cabinet Dimension (W/H)	480 x 540mm / 480 x 270mm / 240 x 540mm 18.90 x 21.26inch / 18.90 x 10.63inch / 9.45 x 21.26inch
Cabinet Resolution	192 x 126
Cabinet Weight (panel)	≤7kg (480 x 540) / ≤4kg (480 x 270) / ≤4kg (240 x 540) ≤15.44lbs (18.90 x 21.26) / ≤8.82lbs (18.90 x 10.63) / ≤8.82lbs (9.45 x 21.26)
Brightness (Nits)	500 (400-800 Adjustable)
Contrast Ratio	7000:1
Maintanance	Front Access
IP Rating	IP50
Max Power Consumption (W/sqm)	≤650
Avg Power Consumption (W/sqm)	≤150
Viewing Angle	160°
Refresh Rate (Hz)	3840
Operating Enviroment	-10° to 40° / 10 to 90% Relative Humidity (non condensing)
Life Span	100,000 Hours

## Display Dimensions

