

HOA SERIES P6 OUTDOOR LED DISPLAY

HOA series outdoor LED solutions are perfect for any billboard or large scale LED wall project. These ultra reliable, high brightness, low power consumption modules also feature an IP65 rating and auto brightness adjustment for the ultimate impact in any climate or weather conditions. Hisense LED modules include cable-less internal construction and rear access for ease of maintenance.



Highlights



Ultra high brightness

With 5,500 nits maximum brightness the display panels can deliver amazingly vivid imagery anywhere during daytime and nighttime conditions.



120° High viewing angle

The extra wide 120° viewing angle is a perfect fit for large groups of people that will view the displays from diverse angles while passing by.



High refresh rate

With uniform color scale and brightness, dynamic performance of LED display could restore the true scenes without any ripples.



Ultra high contrast ratio

LED display could reveal more details, including layers and colors, than traditional displays do.



Long Lifespan

The HOA series boasts an incredibly long lifespan of upto 100000hrs.



Clear and consistent picture

LED display providing a clear and consistent picture throughout it's lifespan.




Effortless set-up and maintenance

LED display could reveal more details, including layers and colors, than traditional displays do.



Durable in Outdoor Environments

The fully waterproof module ensures the TES LED display series with ongoing performance when exposed to high temperature, high-humidity and a variety of natural and unintentional scenarios.



Specifications

HOA6.0-TAM9696R

Pixel Pitch	6
LED Package	SMD copper wire
LED Type	SMD2727
Thickness	135mm x 5.31inch
Module Resolution	32x32
Module Size (WxH)	192 x 192mm / 7.56 x 7.56inch
Cabinet Dimension (WxH)	960(W) x 960(H) / 37.8(W) x 37.8(H)
Cabinet Resolution	160x160
Cabinet Weight (panel)	≤33kg / ≤72.77lbs
Cabinet materials	Metal plate
Brightness (Nits)	5500 Nits
Contrast Ratio	≥5000:1
Maintenance	Rear Access
IP Rating	Front:IP65/Rear:IP54
Max Power Consumption (W/sqm)	≤800
Avg Power Consumption (W/sqm)	≤260
Viewing Angle (H/V)°	≥140 degrees
Refresh Rate (Hz)	>1920~3840
Operating Environment	From -20~60oc
Relative Humidity	10~90%RH
Life Span	≥100,000hrs

Display Dimensions

